



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### · 1.1 Product identifier

· Trade name: **AUTOSOL® Stainless Steel Polish**

### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture** Polishing agent/ Burnishing compound

### · 1.3 Details of the supplier of the safety data sheet

#### · Manufacturer/Supplier:

Dursol-Fabrik Otto Durst GmbH & Co. KG

Martinstr. 22

42655 SOLINGEN

Germany

Tel.: +49 (0)212 - 2718-0

Fax: +49 (0)212 - 208795

www.autosol.de                      www.dursol.de

#### · Further information obtainable from:

Abteilung Produktsicherheit

labor@autosol.de

### · 1.4 Emergency telephone number:

+49 (0)212 - 2718-0

8.00 - 16.00 h

## SECTION 2: Hazards identification

### · 2.1 Classification of the substance or mixture

#### · Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2                      H315 Causes skin irritation.

Eye Irrit. 2                      H319 Causes serious eye irritation.

Aquatic Chronic 3              H412 Harmful to aquatic life with long lasting effects.

#### · Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Not applicable.

R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

#### · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

#### · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 1)

## 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

### Hazard pictograms



GHS07

### Signal word Warning

### Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.

P273 Avoid release to the environment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

### Additional information: Keep out of reach of children.

### 2.3 Other hazards

### Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Xn R65; F R11; N R51/53 R67 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H302; STOT SE 3, H336	10-25%
CAS: 8008-20-6 EINECS: 232-366-4	Kerosine (petroleum) Xn R65 Asp. Tox. 1, H304; Aquatic Chronic 3, H412	10-25%

(Contd. on page 3)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 2)

CAS: 100-37-8 EINECS: 202-845-2	2-diethylaminoethanol C R34; Xn R20/21/22 R10 Flam. Liq. 3, H226; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Acute Tox. 4, H302; STOT SE 3, H335	1-10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol F R11 Flam. Liq. 2, H225	1-10%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### For safety reasons unsuitable extinguishing agents:

Water with full jet

### 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

### 5.3 Advice for firefighters

#### Protective equipment:

No special measures required.

#### Additional information

Cool endangered receptacles with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Not required.

### 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

---

**Trade name: AUTOSOL® Stainless Steel Polish**

---

(Contd. of page 3)

See Section 13 for disposal information.

---

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
  - **Information about fire - and explosion protection:** No special measures required.
  - **7.2 Conditions for safe storage, including any incompatibilities**
  - **Storage:**
  - **Requirements to be met by storerooms and receptacles:** No special requirements.
  - **Information about storage in one common storage facility:** Not required.
  - **Further information about storage conditions:** None.
  - **Storage class:** 12
  - **7.3 Specific end use(s)** No further relevant information available.
- 

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

<b>64-17-5 ethanol</b>
------------------------

WEL   Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
--

- **Additional information:** The lists valid during the making were used as basis.
  - **8.2 Exposure controls**
  - **Personal protective equipment:**
  - **General protective and hygienic measures:**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.
  - **Respiratory protection:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.  
Filter A/P2
  - **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
  - **Material of gloves**  
Natural rubber, NR  
Recommended thickness of the material:  $\geq 0.5$  mm  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- 

(Contd. on page 5)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

---

**Trade name: AUTOSOL® Stainless Steel Polish**

---

(Contd. of page 4)

**· Penetration time of glove material**

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling
- 

## SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties****· General Information****· Appearance:**

Form: Pasty

Colour: White

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value at 20 °C:** 9.2

**· Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

**· Ignition temperature:**

**Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

**· Explosion limits:**

**Lower:** Not determined.

**Upper:** Not determined.

· **Vapour pressure at 20 °C:** 23 hPa

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

**· Solubility in / Miscibility with**

**water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

**· Viscosity:**

**Dynamic:** Not determined.

**Kinematic:** Not determined.

(Contd. on page 6)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 5)

· **9.2 Other information** No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

### 64742-49-0 Naphtha (petroleum), hydrotreated light

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	2800 mg/kg (rabbit)
Inhalative	LC50 (4 h)	>23.3 mg/l (rat)

### 100-37-8 2-diethylaminoethanol

Oral	LD50	1300 mg/kg (rat)
Inhalative	LC50 (4 h)	5 mg/l (mouse)

### 64-17-5 ethanol

Oral	LD50	10470 mg/kg (rat) (OECD 401 (Acute Oral Toxicity))
Dermal	LD50	>2000 mg/kg (rabbit) (OECD 402 (Acute Dermal Toxicity))
Inhalative	LC50 (4 h)	117-125 mg/l (rat) (OECD 403 (Acute Inhalation Toxicity))

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitisation:** No sensitising effects known.
- **Additional toxicological information:**  
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

— GB —

(Contd. on page 7)



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 6)

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

##### 64-17-5 ethanol

LC50 (48 h) | 12340 mg/l (daphnia)

LC50 (96 h) | 13000 mg/l (fish)

### · 12.2 Persistence and degradability

##### 64-17-5 ethanol

BCF | 3.2 mg/l (Bioconcentrationfactor)

log POW | -0.32 (log POW)

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

#### · Ecotoxicological effects:

· **Remark:** Harmful to fish

#### · Additional ecological information:

##### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### · 14.1 UN-Number

· ADR, ADN, IMDG, IATA

Void

### · 14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA

Void

(Contd. on page 8)

— GB —



# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 05.11.2014

Revision: 05.11.2014

Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 7)

· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture  
No further relevant information available.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
- R34 Causes burns.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R67 Vapours may cause drowsiness and dizziness.

(Contd. on page 9)

GB



# Safety data sheet

according to 1907/2006/EC, Article 31

---

Trade name: AUTOSOL® Stainless Steel Polish

---

(Contd. of page 8)

· **Department issuing MSDS:**

Dursol-Fabrik Otto Durst GmbH & Co. KG  
Martinstraße 22  
42655 Solingen  
Germany  
Abteilung F&E / Produktsicherheit

· **Contact:** labor@autosol.de

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
Flam. Liq. 2: Flammable liquids, Hazard Category 2  
Flam. Liq. 3: Flammable liquids, Hazard Category 3  
Acute Tox. 4: Acute toxicity, Hazard Category 4  
Acute Tox. 3: Acute toxicity, Hazard Category 3  
Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B  
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2  
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
Asp. Tox. 1: Aspiration hazard, Hazard Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3