

Printing date 10.08.2016 V - 4 Revision: 10.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: S100 DRY LUBE CHAIN SPRAY

· Article number: 2380, 2381

- 1.2 Relevant identified uses of the substance or mixture and uses advised against Void
- · Application of the substance / the mixture Maintenance product
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dr.O.K.Wack Chemie GmbH

Bunsenstrasse 6 D - 85053 Ingolstadt

Tel. +49 841-6350 Fax +49 841-63558

www.wackchem.com wack.info@wackchem.com

- · Further information obtainable from: Safety department
- · 1.4 Emergency telephone number: During business hours: +49 841 63523

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- · Hazard pictograms GHS02, GHS07
- Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains Fatty acids, tall-oil, reaction products with boric acid (H3BO3) and diethanolamine. May produce an allergic reaction.

(Contd. on page 2)



V - 4 Printing date 10.08.2016 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description**: Mixture of the substances with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	25-<30%
CAS: 106-97-8 EINECS: 203-448-7	butane The image is a second of the second	10-<20%
CAS: 74-98-6 EINECS: 200-827-9	propane Flam. Gas 1, H220; Press. Gas C, H280	10-<20%
CAS: 1569-01-3 EINECS: 216-372-4 Reg.nr.: 01-2119474443-37-0000	1-propoxypropan-2-ol Flam. Liq. 3, H226; Eye Irrit. 2, H319	10-<15%
CAS: 64742-94-5 EINECS: 265-198-5 Reg.nr.: 01-2119463583-34-	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	<2,5%
CAS: 91770-03-5 EINECS: 294-785-9 Reg.nr.: 01-2119961359-26-xxxx	Fatty acids, tall-oil, reaction products with boric acid (H3BO3) and diethanolamine Skin Sens. 1B, H317	<7%
CAS: 28016-00-4 Reg.nr.: 28016-00-4248-778-2	Zinkbis-(dinonylnaphtalinsulfonat) Skin Irrit. 2, H315; Eye Irrit. 2, H319	1-<3%

- · SVHC None
- · Additional information:

EINECS: 294-785-9 specific concentration limit.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out into the fresh air.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: After contact with skin, wash immediately with plenty of soap and water.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing:
- If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

V - 4 Printing date 10.08.2016 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 2)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Danger of bursting.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wear protective clothing.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Avoid contact with skin and eyes.

Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

(Contd. on page 4)



Printing date 10.08.2016 V - 4 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

·DNELs		
64-17-5 €	ethanol	
Oral	DNEL system. effects (long-term)	87 mg/kg KG/Tag (Consumer)
Dermal	DNEL systemic effects	343 mg/kg (Worker)
	DNEL system. effects (long-term)	206 mg/kg KG/Tag (Consumer)
Inhalative	DNEL system. effects (long-term)	114 mg/m³ (Consumer)
		950 mg/m³ (Worker)
	DNEL local effects (short-term)	950 mg/m³ (Consumer)
		1900 mg/m³ (Worker)
1569-01-	3 1-propoxypropan-2-ol	
Oral	DNEL system. effects (long-term)	11 mg/kg KG/Tag (Consumer)
Dermal	DNEL system. effects (long-term)	36 mg/kg KG/Tag (Consumer)
		82,5 mg/kg KG/Tag (Worker)
Inhalative	DNEL system. effects (long-term)	38 mg/m³ (Consumer)
		263 mg/m³ (Worker)
64742-94	1-5 Solvent naphtha (petroleum), l	heavy arom.
Inhalative	DNEL system. effects (long-term)	32 mg/m³ (Consumer)
		151 mg/m³ (Worker)
PNECs	<u> </u>	
64-17-5 e	ethanol	
PNEC 0,	.79 mg/l (Meerwasser)	
0,	.96 mg/l (fresh water)	
1569-01-	3 1-propoxypropan-2-ol	
PNEC 0,	.01 mg/l (Meerwasser)	
0,	.1 mg/l (fresh water)	

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Ensure good ventilation/exhaustion at the workplace.

Keep away from foodstuffs, beverages and feed.

Be sure to clean skin thoroughly after work and before breaks.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- Protection of hands:

Preventive skin protection by use of skin-protecting agents is recommended.

After each cleaning use treatment creams, for very dry skin greasy ointments.

(Contd. on page 5)

Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.08.2016 V - 4 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 4)

- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical propertie	· 9.1	Information or	hasic phy	sical and c	hemical prope	erties
--	-------	----------------	-----------	-------------	---------------	--------

· General Information

Appearance:

Form:
Colour:
Yellow-brown
Odour:
Product specific
Not determined.

pH-value:
Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -44 °C

· Flash point: -97 °C

Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 365 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

1.3 Vol %

· Explosion limits:

Lower:

Upper:15,0 Vol %· Vapour pressure at 20 °C:8300 hPa· Density:Not determined.

Relative density

Relative density

Vapour density

Evaporation rate

Not determined.

Not determined.

Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



V - 4 Printing date 10.08.2016 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 5)

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Store away from oxidising agents.
- · 10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
64-17-5 et	64-17-5 ethanol	
Oral	LD50	10470 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
Inhalative	LC50/4 h	>20 mg/l (mouse)
106-97-8 k	outane	
Inhalative	LC50/4 h	658 mg/l (rat)
1569-01-3 1-propoxypropan-2-ol		
Oral	LD50	> 2000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)
64742-94-	5 Solvent	naphtha (petroleum), heavy arom.
Oral	LD50	6318 mg/kg (rat) (OECD 401)
Dermal	LD50	> 2000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	> 4,7 mg/l (rat) (OECD 403)
28016-00-	4 Zinkbis-	(dinonylnaphtalinsulfonat)
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>20000 mg/kg (rabbit)

- · Specific symptoms in biological assay: Not determined
- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met:
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.08.2016 V - 4 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 6)

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	· Aquatic toxicity:	
64-17-5 ethanol		
EC50/48h	> 10000 mg/l (daphnia magna)	
LC50/48h	8140 mg/l (leuciscus idus)	
1569-01-3 1-propoxypropan-2-ol		
LC50/96h (static)	> 100 mg/l (oncorhynchus mykiss)	
EC50 (static)	3800 mg/l (Bacteria)	
LC50/48h (static)	> 100 mg/l (daphnia magna)	
64742-94-5 Solvent naphtha (petroleum), heavy arom.		
EC50/72h	1-3 mg/l (algae)	
EC50/48h	3-10 mg/l (daphnia magna)	

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

14 06 03* other solvents and solvent mixtures

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS · IMDG AEROSOLS

(Contd. on page 8)



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Trade name: \$100 DRY LUBE CHAIN SPRAY

	(Contd. of page
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre:
	Category A. For AEROSOLS with a capacity above 1 litre:
	Category B. For WASTE AEROSOLS: Category C, Clear of
	living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class 1
	except for division 1.4. For AEROSOLS with a capacity
	above 1 litre: Segregation as for the appropriate subdivisio
	of class 2. For WASTE AEROSOLS: Segregation as for the
	appropriate subdivision of class 2.
14.7 Transport in bulk according to Anne.	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
. , , , , ,	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 9)



V - 4 Printing date 10.08.2016 Revision: 10.08.2016

Trade name: S100 DRY LUBE CHAIN SPRAY

(Contd. of page 8)

- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* * Data compared to the previous version altered.