

e1 0758 (5)



Street-legal component approval certificate

for non-original motorcycle exhaust system



502360

Component approval No.: e1*97/24*2009/108/5/VII*0758*01

Issued by: Kraftfahrt-Bundesamt,
Fördestraße 16, DE-24944 Flensburg

Place & date of type-approval: Flensburg, 27.07.2010

Report No.: 09-00046-CM-GBM-01

Issued by: TÜV SÜD AUTOMOTIVE GMBH
TÜV SÜD Gruppe
DE-85748 Garching

Date of issue: 14.07.2010

Approval identification: e1 0758 (5)

Type and version of exhaust: P-KAT-025

Technical unit:

Technical unit, consisting out of one catalytic converter according to drawing no. KATAL. D62X65 400CPSI 200gft 1/28/1, ø 62, length 65 mm.

Marking:

Engraved by laser on sleeve

Field of application:

Manufacturer-Trade mark	Commercial description	Vehicle type (and no. of homologation)	Engine type	Component parts, dimensions in mm	Dimensions of the part in mm or original part / replacement part	Part no. or Homologation no.
DUCATI	Monster 1100 / ABS Monster 1100 S / ABS	M5 (e3*0497*)	1078AC	Header pipes	Original parts	-
				Link pipe right	-	L-DIOS03R
	Link pipe left		-	L-DIOS03L		
	Monster 796 / ABS Monster 696 / ABS		796A2B	Catalytic converter right	ø 62x65	P-KAT-025
				Catalytic converter left	ø 62x65	P-KAT-025
	Monster 696 / ABS		696A2	Rear silencer right (outlet pipe ø 32)	hexagonal 103x130 mm Length without end caps 300 mm	M-HZ037 e1*0760*(9)
Rear silencer left (outlet pipe ø 32)		hexagonal 103x130 mm Length without end caps 300 mm		M-HZ037 e1*0760*(9)		

To be filled out by Akrapovič representative:

Date of purchase: Issued by:

Stamp & signature:

Muffler repack kit service intervals

The durability of the damping material depends on the type of motorcycle, riding style, mileage etc. Normally, single and twin cylinder engines produce a stronger exhaust gas wave pulse and a higher temperature. Often, riding on a race track requires noise control. The insulating material should be replaced when you notice any visual changes on the muffler sleeve material or when the muffler exceeds the noise limit. Please check the muffler visually before every season.

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Date: _____

Performed by: _____

Stamp & signature: _____

Maintenance

1. Clean the titanium muffler outer sleeves with a multi-purpose spray lubricant (WD-40 or equivalent) and carbon-fiber outer sleeves with soft and dry cloth. Do not use aggressive chemical cleaners, because they can damage the sticker. A change in the color of the exhaust system is normal due to the high temperatures.

2. The wearing out of the muffler silencing material depends on the type of the motor and riding style. Contact your dealer/serviceman if visible changes appear on muffler's outer sleeve or the noise level is increased.

3. Periodically make sure all the bolts are sufficiently tight.

Exclusion of Certain Liability

1. The manufacturer, importer or dealer shall not be liable for any incidental damage including personal injury or any other damages caused by improper installation or operation of the Akrapovič exhaust system. When installing the Akrapovič exhaust system be careful that the exhaust system does not touch other parts sensitive to high temperature.

2. Akrapovič makes no representation or warranties with regard to damage caused by the improper installation, use and maintenance of the Akrapovič exhaust system. The warranty is limited to defects recognized by our technical department and to normal use, and excludes items subject to normal wear (gaskets and damping wool). The guarantee is void in case of accident, modification, improper or competition use.

3. Do not attempt to install the Akrapovič exhaust system on a motorcycle for which it was not made or tested by Akrapovič.

4. When the exhaust system gets very hot during operation, be careful not to burn yourself on the exhaust system or parts which are in direct contact with it, even when the motor is not running. Also protect other people, especially children, from the injuries mentioned above.

5. In some cases Akrapovič exhaust system kits contain chemical products (ceramic anti-seizing grease). Handle with care, do not inhale or swallow. Avoid excessive contact with skin, eyes or mucous membranes. Keep out of the reach of children.

6. Technical specifications of Akrapovič exhaust systems and related products subject to change without notice.