



| Pos | Qty | Part No. | Description | Ordernumber |
|---------------------|-----|--------------|-------------------------------------|---|
| 1 | 1 | 900024 | Muffler BOS Oval120 Stainless Steel | 1111575S - Stainless Steel |
| 1 | 1 | 900025 | Muffler BOS Oval120 Carbon Steel | 1111575Cs - Carbon Steel |
| | | 80206 | Mounting Parts: | |
| 2 | 1 | 72265 | Link Pipe 11575 | Weight: |
| 3 | 1 | 64684 | Mounting Bracket | Stock: 4,6 kg |
| 4 | 2 | 14140 | Bolt M6x16 | Bos: 3,8 kg |
| 5 | 2 | 14087 | Pull Spring 48 mm. | |
| 6 | 1 | 64558 | Clamp 43-47 | |
| | | | | Noiselevel: @ 5000 rpm |
| | | | | Stock: Specified 88,0 dB(A) |
| | | | | Measured 86,5 dB(A) |
| | | | | Bos: With DBeater 87,0 dB(A) |
| | | | | Open 91,3 dB(A) |
| | | | | Performance |
| | | | | Stock: 102,5 Hp / 9485 rpm |
| | | | | Bos: 104,2 Hp / 9568 rpm |
| | | | | Max. Hp incr.: + 2,1 Hp / 8468 rpm |
| | | | | Max Nm incr.: + 2,7 Nm / 2475 rpm |
| | | | | Tips |
| | | | | In order to avoid smudges and fingerprints burning into the surface it is imperative to clean the exhaust before starting the engine, burnt in stains are very difficult to remove. |
| | | | | After 300 miles or 500 kms. check all nuts and bolts and retighten if necessary. |
| Extra Parts: | | | | |
| | | 50119 | DBeater Ø32 Hyper | |